




# HTC Touch Camera Lens Replacement

This guide will successfully lead its readers to replacing the camera on the phone.

Written By: Sehyun



## INTRODUCTION

Warning: Always be sure you are grounded whenever handling any of the circuit or logic boards.

---



### TOOLS:

- [iFixit Opening Tools](#) (1)
  - [T5 Torx Screwdriver](#) (1)
-

## Step 1 — Camera Lens



- Remove the back panel by sliding it up.

## Step 2



- Remove the battery.



### Step 3



- Remove the 4 torx-head screws in the corners of the phone using the T5 Torx Screwdriver.

### Step 4



- Use the plastic opening tool to remove the front panel from the phone.
- Unplug the front button cable from the inside of the phone.

## Step 5



- Unscrew the torx-head screws at the base of the LCD screen using the T5 Torx Screwdriver.

## Step 6



- Separate the motherboard from the black plastic casing.
- Unplug the black and red wire from the motherboard.
- Unplug the black and red wire from the black plastic casing.




## Step 7



- Lift the black lever next to the orange ribbon cable to remove the LCD Screen.

## Step 8



- Remove the camera lens from the motherboard using the plastic opening tool.

To reassemble your device, follow these instructions in reverse order.

This document was last generated on 2017-08-05 07:46:10 AM.